

| Specification | Description |
|---|---|
| General Specifications | |
| Printer Type | LMP |
| Number Of Print Columns | 136 Columns |
| Number Of Paper Paths | Single paper path |
| Printing Colour | Black |
| Print Method | Impact Line Matrix |
| Printer Dimension | 660 mm X 546 mm X 914mm |
| Weight | 52Kg Shipping Weight: 165 lbs (75Kg) |
| Manufacturer Warranty | 1 Year Onsite warranty |
| Printing Performance | |
| Paper Feed Speed (Inches Per Second) | 20 |
| Print Speed - High Speed (LPM) - UCC | 1000 |
| Print Speed - High Speed (LPM) - LCC | 856 |
| Print Speed - Data Processing (LPM) - UCC | 750 |
| Print Speed - Data Processing (LPM) - LCC | 600 |
| Print Speed - Near Letter Quality (LPM) - UCC | 400 |
| Print Speed - Near Letter Quality (LPM) - LCC | 306 |
| Print Speed - Graphics (IPM) 60X48 dpi | 125 |
| Print Speed - Graphics (IPM) 60X72 dpi | 83 |
| Print Speed - Graphics (IPM) 60X96 dpi | 42 |
| Fonts Supported | NLQ Serif, NLQ Sans Serif, Data Processing, High Speed, OCR A, OCR B |
| Print Attributes | Bold, Italic, Double Width, Double Height, Overstrike, Underline, Subscript and Superscript |
| Pitch Supported (CPI - Characters Per Inch)) | 10, 12, 13.3, 15, 17.1, 20 (except NLQ for 20 pitch) |

| | |
|-------------------------------------|---|
| Line Spacing (LPI - Lines Per Inch) | 6, 8, 10.3, n/72, n/216 |
| Printable Width | Up to 13.6" (345 mm) |
| Resident Character Sets | 99 plus character sets including ECMA Latin 1, DEC Multinational, IBM Code Page 437 and 850, OCR A, OCR B, UTF8 encoded Unicode |
| Resident Bar Codes | 30 resident symbologies, including Code 39, EAN 8/13, UPC A/E, Postnet, Royal Mail, Interleaved 2 of 5 and PDF 417 |
| Indian Language printing | Bi-lingual (Devanagiri) Printing Capability |
| Dot Size | 16.7 mil |
| Paper Handling Features | □ |
| Types of Paper Handled | Continuous, Fan Folded, Edge-perforation |
| Paper Width Supported | 76mm to 432mm |
| Number of Copies | Carbon Multipart : 4 copies Carbonless multipart: 6 copies |
| Paper Quality and Thickness | upto 0.64mm max. weight of 163gm/sq.mts |
| Paper Feed (Input) | Bottom Feed |
| Paper Path | Straight through paper path with easy-load dual adjustable tractors |
| Paper Path (Exit) | Rear Exit Path |
| Built-in Functions | □ |
| Paper-out Detector and Alarm | yes, printer will not print without paper |
| Paper Motion Detector and Alarm | yes |
| Integrated Print Management | Yes |
| Ribbon Life Monitor | Yes |
| Black Back Form Sensor | Yes |
| Front Paper Tray | Yes |
| Rear Pull Out Paper Tray | Yes |
| Extended Door Kit | NO |
| High Rear Paper Tray | yes |
| Acoustic Shroud | Yes |
| Front Paper Access System | YES |

| | |
|---|---|
| Connectivity, Drivers and Emulations | |
| Interface - Parallel (Centronics) | yes(Optional) |
| Interface - Serial (RS 232C) | yes |
| Interface - USB | yes |
| Interface - LAN (Ethernet) | yes |
| Interface - WLAN (Wireless) | |
| Printer Drivers | Standard SAP Device Types, Windows 95/98/XPVISTA/NT/2000/2003/2008/7/8 |
| Printer Support Software | WeP Printronix PrintNet Enterprise Remote Management Software |
| Emulation Standard | Printronix P-Series, P-Series XQ, Serial Matrix, IBM ProPrinter III XL, Epson FX-1050 |
| Emulation Optional | ANSI, IPDS, PCL2, DEC LG, TN5250/TN3270 |
| Power and Operating Conditions | |
| Input Voltage | Auto Ranging 100-120 VAC, 200-240 VAC |
| Frequency | 50/60 Hz |
| Power Consumption - Stand-by | less than 14watts |
| Power Consumption - Operating mode | 300 watts |
| Operating Temperature | 50° to 104° F (10° to 40° C) |
| Energy Star Compliance | Energy Star - Less than 14 Watts |
| Safety and Reliability | |
| MTBF | 10,000 Hours (Hours at 25% duty cycle and 25% page density) |
| Life of Cartridge Ribbons | 30,000 Pages (ISO 19752 Test page) |
| Noise level (As per ISO 7779) | 65.5 dBA |
| Whats In the Box | Description |
| Whats in the Box | |
| Power Cable | yes |

| Black Ribbon Cartridge | yes |
|---------------------------------------|-------------|
| Warranty manual | yes |
| Driver CD | yes |
| User Manual | yes |
| Interface Cable - Parallel | yes |
| Serial converter | yes |
| Remote Operation Panel Software CD | yes |
| Printer configuration page | yes |
| Warranty registration card | yes |
| Consumables | Description |
| Consumables & Accessories | |
| Ribbon Cartridge | □ |
| Print Head | |
| Ribbon Refills | □ |
| Toner Cartridge | |
| Line Matrix Spools | □ |