

Specification	Description
General Specifications	
Printer Type	LMP
Number Of Print Columns	136 Columns
Number Of Paper Paths	Single paper path
Printing Colour	Black
Print Method	Impact Line Matrix
Printer Dimension	686mm X 737mm X 1029mm
Weight	91 Kg Shipping Weight: 165 lbs (120Kg)
Manufacturer Warranty	1 Year Onsite warranty
Printing Performance	
Paper Feed Speed (Inches Per Second)	25
Print Speed - High Speed (LPM) - UCC	1500
Print Speed - High Speed (LPM) - LCC	1289
Print Speed - Data Processing (LPM) - UCC	1125
Print Speed - Data Processing (LPM) - LCC	900
Print Speed - Near Letter Quality (LPM) - UCC	600
Print Speed - Near Letter Quality (LPM) - LCC	459
Print Speed - Graphics (IPM) 60X48 dpi	187
Print Speed - Graphics (IPM) 60X72 dpi	127
Print Speed - Graphics (IPM) 60X96 dpi	61
Fonts Supported	NLQ Serif, NLQ Sans Serif, Data Processing, High Speed, OCR A, OCR B
Print Attributes	Bold, Italic, Double Width, Double Height, Overstrike, Underline, Subscript and Superscript

Pitch Supported (CPI - Characters Per Inch)	10, 12, 13.3, 15, 17.1, 20 (except NLQ for 20 pitch)
Line Spacing (LPI - Lines Per Inch)	6, 8, 10.3, n/72, n/216
Printable Width	Up to 13.6" (345 mm)
Resident Character Sets	Over 100 multinational sets including IBM World Trade, ECMA Latin 1, DEC Multinational, IBM Code Page 437 and 850, OCR A, OCR B, UTF8 encoded Unicode
Resident Bar Codes	30 resident symbologies, including Code 39, EAN 8/13, UPC A/E, Postnet, Royal Mail, Interleaved 2 of 5 and PDF 417
Indian Language printing	Bi-lingual (Devanagiri) Printing Capability
Dot Size	16.7 mil
Paper Handling Features	
Types of Paper Handled	Continuous, Fan Folded, Edge-perforation
Paper Width Supported	76mm to 432mm
Number of Copies	Carbon Multipart : 4 copies Carbonless multipart: 6 copies
Paper Quality and Thickness	upto 0.64mm max. weight of 163gm/sq.mts
Paper Feed (Input)	Bottom Feed
Paper Path	Straight through paper path with easy-load dual adjustable tractors
Paper Path (Exit)	Rear Exit Path
Built-in Functions	
Paper-out Detector and Alarm	yes, printer will not print without paper
Paper Motion Detector and Alarm	yes
Integrated Print Management	Yes
Ribbon Life Monitor	Yes
Black Back Form Sensor	Yes
Front Paper Tray	Yes
Rear Pull Out Paper Tray	Yes
Extended Door Kit	NO

High Rear Paper Tray	yes
Acoustic Shroud	Yes
Front Paper Access System	YES
Connectivity, Drivers and Emulations	□
Interface - Parallel (Centronics)	yes(Optional)
Interface - Serial (RS 232C)	yes
Interface - USB	yes
Interface - LAN (Ethernet)	yes
Interface - WLAN (Wireless)	
Printer Drivers	Standard SAP Device Types, Windows 95/98/XPVISTA/NT/2000/2003/2008/7/8
Printer Support Software	WeP Printronix PrintNet Enterprise Remote Management Software
Emulation Standard	Printronix P-Series, P-Series XQ, Serial Matrix, IBM ProPrinter III XL, Epson FX-1050
Emulation Optional	ANSI, IPDS, PCL2, DEC LG, TN5250/TN3270
Power and Operating Conditions	□
Input Voltage	Auto Ranging 100-120 VAC, 200-240 VAC
Frequency	50/60 Hz
Power Consumption - Stand-by	less than 5 watts
Power Consumption - Operating mode	435 watts
Operating Temperature	50° to 104° F (10° to 40° C)
Energy Star Compliance	Energy Star - Less than 5 Watts
Safety and Reliability	
MTBF	10,000 Hours (Hours at 25% duty cycle and 25% page density)
Life of Cartridge Ribbons	30,000 Pages (ISO 19752 Test page)

Noise level (As per ISO 7779)	52 dBA
Whats In the Box	Description
Whats in the Box	
Power Cable	yes
Black Ribbon Cartridge	yes
Warranty manual	yes
Driver CD	yes
User Manual	yes
Interface Cable - Parallel	yes
Serial converter	yes
Remote Operation Panel Software CD	yes
Printer configuration page	yes
Warranty registration card	yes
Consumables	Description
Consumables & Accessories	
Ribbon Cartridge	□
Print Head	
Ribbon Refills	□
Toner Cartridge	
Line Matrix Spools	□