

Specification	Description
General Specifications	
Printer Type	LMP
Number Of Print Columns	136 Columns
Number Of Paper Paths	Single paper path
Printing Colour	Black
Print Method	Impact Line Matrix
Printer Dimension	686 mm X 737 mm X 914mm
Weight	91Kg Shipping Weight: 264lbs (120Kg)
Manufacturer Warranty	1 Year Onsite warranty
Printing Performance	
Paper Feed Speed (Inches Per Second)	39
Print Speed - High Speed (LPM) - UCC	2000
Print Speed - High Speed (LPM) - LCC	1700
Print Speed - Data Processing (LPM) - UCC	1500
Print Speed - Data Processing (LPM) - LCC	1200
Print Speed - Near Letter Quality (LPM) - UCC	800
Print Speed - Near Letter Quality (LPM) - LCC	615
Print Speed - Graphics (IPM) 60X48 dpi	250
Print Speed - Graphics (IPM) 60X72 dpi	167
Print Speed - Graphics (IPM) 60X96 dpi	83
Fonts Supported	NLQ Serif, NLQ Sans Serif, Data Processing, High Speed, OCR A, OCR B
Print Attributes	Bold, Italic, Double Width, Double Height, Overstrike, Underline, Subscript and Superscript

Pitch Supported (CPI - Characters Per Inch) 10, 12, 13.3, 15, 17.1, 20 (except NLQ for 20 pitch)

Line Spacing (LPI - Lines Per Inch) 6, 8, 10.3, n/72, n/216

Printable Width Up to 13.6" (345 mm)

Resident Character Sets Over 100 multinational sets including IBM World Trade, ECMA Latin 1, DEC Multinational, IBM Code Page 437 and 850, OCR A, OCR B, UTF8 encoded Unicode

Resident Bar Codes 30 resident symbologies, including Code 39, EAN 8/13, UPC A/E, Postnet, Royal Mail, Interleaved 2 of 5 and PDF 417

Indian Language printing Bi-lingual (Devanagiri) Printing Capability

Dot Size 16.7 mil

Paper Handling Features

Types of Paper Handled Continuous, Fan Folded, Edge-perforation

Paper Width Supported 76mm to 432mm

Number of Copies Carbon Multipart : 4 copies Carbonless multipart: 6 copies

Paper Quality and Thickness upto 0.64mm max. weight of 163gm/sq.mts

Paper Feed (Input) Bottom Feed

Paper Path Straight through paper path with easy-load dual adjustable tractors

Paper Path (Exit) Rear Exit Path

Built-in Functions

Paper-out Detector and Alarm yes, printer will not print without paper

Paper Motion Detector and Alarm yes

Integrated Print Management Yes

Ribbon Life Monitor Yes

Black Back Form Sensor Yes

Front Paper Tray Yes

Rear Pull Out Paper Tray Yes

Extended Door Kit NO

High Rear Paper Tray yes

Acoustic Shroud	Yes
Front Paper Access System	YES
Connectivity, Drivers and Emulations	
Interface - Parallel (Centronics)	yes(Optional)
Interface - Serial (RS 232C)	yes
Interface - USB	yes
Interface - LAN (Ethernet)	yes
Interface - WLAN (Wireless)	
Printer Drivers	Standard SAP Device Types, Windows 95/98/XPVISTA/NT/2000/2003/2008/7/8
Printer Support Software	WeP Printronix PrintNet Enterprise Remote Management Software
Emulation Standard	Printronix P-Series, P-Series XQ, Serial Matrix, IBM ProPrinter III XL, Epson FX-1050
Emulation Optional	ANSI, IPDS, PCL2, DEC LG, TN5250/TN3270
Power and Operating Conditions	
Input Voltage	Auto Ranging 100-120 VAC, 200-240 VAC
Frequency	50/60 Hz
Power Consumption - Stand-by	less than 5 watts
Power Consumption - Operating mode	450 watts
Operating Temperature	50° to 104° F (10° to 40° C)
Energy Star Compliance	Energy Star - Less than 5 Watts
Safety and Reliability	
MTBF	10,000 Hours (Hours at 25% duty cycle and 25% page density)
Life of Cartridge Ribbons	30,000 Pages (ISO 19752 Test page)
Noise level (As per ISO 7779)	55 dBA