

Specification	Description
<b>General Specifications</b>	
Printer Type	HSDMP
Number Of Pins	24 pin
Number Of Print Columns	136 Column
Number Of Paper Paths	front 1 and front 2 paper paths
Printing Colour	Black
Print Method	serial dot matrix printer
Printer Dimension	670 mm X 390 mm X 320 mm
Weight	21 Kg
<b>Printing Performance</b>	
Print Direction	Bi-directional, Logic seeking / Bi-Directional for Image and Graphics Printing
Throughput - Pages Per Hour - Draft Pica (10 Cpi)	600 Page per Hour
Print Speed - Super Speed Draft (15 Cpi)	900
Print Speed - Speed Draft (12 Cpi)	780
Print Speed - Draft Pica (10 Cpi)	650
Print Speed - NLQ Pica (10 Cpi)	267
Print Speed - LQ Pica (10 Cpi)	133
Work Load	50,000(*) Pages per Month
Resident Fonts	Draft, Courier, Gothic, Prestige, Present, Script, OCR-A, OCR-B
Bar Code	UPC/A, UPC/E, EAN8, EAN13 - UPC/EAN ADD-ON 5, UPC/EAN ADD-ON 2 - Code 39 - Code 128 - Code 11- Code 93 - MSI - Postnet - Codabar - 2/5 Interleaved -2/5 Matrix - 2/5 Industrial - Code GP - C25-3BAR - Code BCD - 2/5 Bidirectional
Print Attributes	Bold, Italic, Underline, Wide Font, Super & Subscribing
Indian Language Printing	Devanagari

## Paper Handling Features

Paper Feed - Continuous	front loading (Front push tractor 4 pin (BASE CONFIGURATION) Additional front push tractor 4 pin (optional))
Number Of Copies	1 + 7
Continuous Paper Width	Fanfold width 76 to 432 mm (3 to 17 inches)
Paper Thickness	thickness 0,635 mm (0,025 inches)

## Built-In Functions

Short Tear Off	Yes (Zero Tear Off)
Paper Parking	Yes (Automatic paper parking of continuous form)

## Connectivity, Drivers And Emulations

Interface - Parallel	Yes (Parallel - Ethernet 10/100)
Interface - Serial	Yes
Interface - USB	Yes (USB 2.0 Plug & play (Windows environment))
Print Buffer	128 KB
Printer Drivers	Windows 9X/2000/XP/Vista, 7, NetViewMaster (remote printer management SW) and Internal WEB Page (both available with LAN interface)
Printer Emulation	Epson® ESC/P LQ Series, IBM® Proprinter XL24, IBM® Personal Printer 2391, ANSI, DEC PPL2

## Power And Operating Conditions

Input Voltage	100V - 240V
Frequency	60 Hz - 50 Hz
Power Consumption - Stand-By	116W Max
Power Consumption - Operating Mode	116W Max

## Safety And Reliability

MTBF	20,000 hours
Life Of Printhead	800 Millions Characters
Life Of Ribbon Cartridge	15 Millions Characters
Noise Level	54 dBA