

Specification	Description
General Specifications	
Printer Type	POS Printer
Print Technology	Direct Thermal
Printing Colour	Black
Dimensions	
Weight	
Manufacturer Warranty	1 Year Onsite warranty
Best Suited For	Hotels & Restaurants, Jewellery Shops, Garments, Departmental Stores, Toll Gates & Parking Lots, Mall Food Courts, Book Shops, PDS, Govt. Projects
Printing Performance	
Printing Speed	160mm/sec
Character Matrix (Size)	
Printing Width (Maximum Characters Per Line)	
Print Resolution	203 x 203 DPI
Fonts Supported	
Barcode Printing	UPC-A/UPC-E/JAN13(EAN13)/JAN8 (EAN8)/CODARBAR/ITF/CODE39/CODE93/CODE128
Paper Cutter Type	Auto
Auto paper Reciever	
Black Mark Mode	
Paper Handling Features	
Paper Supply Method (Paper Path)	Top load
Print Media Supported	Roll Paper
Maximum Roll Paper Diameter	83 mm
Maximum Roll Paper Width	80 mm
Paper Thickness	0.06 ~ 0.08 mm
Multi-part Printing	
Connectivity, Drivers And	

Emulations	
Interface - Parallel	Yes
Interface - Serial	Yes
Interface - USB	Yes
Interface - Bluetooth	
Interface - LAN	
Print Buffer Size	8 KB
Printer Drivers	Win 9X/Win2000/WinME/WinNT/Win XP/WinVista and Win7
Printer Emulation	ESC/POS, STAR
Interface - USB+SERIAL+ETHERNET	
interface- DK port	
Interface - Parallel+USB	Yes
Logo Storage memory	60 KB
Power And Operating Conditions	
Power Supply	External AC Adaptor (included)
Input Voltage	AC 110 - 240V
Output Voltage	24 V, 2.5A
Frequency	50-60Hz
DK port voltage	24 V, 1 A
Power Consumption - Idle Mode	
Power Consumption - Operating Mode	
Working on Battery	No
Battery Type	Not Applicable
Battery Capacity	Not Applicable
Battery Output	Not Applicable
Battery Charger Input	Not Applicable
Battery Charger Output	Not Applicable
Operating Temperature	5-45°C

Storage Temperature	-10-50°C
Operating Humidity	10-90% RH (Except for Paper), storage: 10- 90%
Safety And Reliability	
MCBF - Printer	52 Million Lines
Life Of Printhead	150KM
Life of Auto cutter	1.5 million cuts
Life Of Ribbon Cartridge	
Noise Level	
EMI	